

	Type of oscillator		Rated frequency [MHz]	Input voltage/ current [V]/[mA]	Frequency stability* [ppm]	Output signal	Frequency trimming M-mech. V-voltage R-resist.
OCXO	OCXO10	HC 3410	3 - 25	12/100	±0,3	sin	V
		HC 3414	3 - 25	12/100	±0,2	HCMOS	R
		HC 3415	3 - 25	12/100	±0,2	HCMOS	R
		HC 3416	3 - 25	12/100	±0,2	sin	R
		HC 3417	5 - 40	12/110	±0,05	sin	R/V
		HC 3418	5 - 40	12/110	±0,05	ACMOS	R/V
	OCXO12	HC 3412	5 -25	5/50	±0,5	sin	V
TCXO	TCXO6	HC 3306	4 - 40	5/3	±2,5	sin	V,M
		HC 3307	4 - 40	5/3	±2,5	sin	M
		HC 3321	4 - 40	5/15	±2,5	HCMOS	V,M
		HC 3322	4 - 40	5/15	±2,5	HCMOS	M
		HC 3323	4 - 40	3,3/10	±2,5	HCMOS	V,M
		HC 3324	4 - 40	3,3/10	±2,5	HCMOS	M
CXO	CXO	HC 3631	4 - 80	5/50	±1000	TTL	-
		HC 3632	4 - 80	5/50	±100	TTL	-
		HC 3633	4 - 80	5/50	±1000	TTL	-
		HC 3634	4 - 80	5/50	±100	TTL	-
		HC 3635	4 - 80	5/50	±80	TTL	-
		HC 3636	4 - 80	5/50	±1000	TTL	-
		HC 3637	4 - 80	5/50	±100		